

Technical data sheet

CARO 120 Soapstone

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Wood storage panel	
With wood storage panel	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Sand	✓
Cladding	
Soapstone	✓
Natural stone porto	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Corian [®]	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓
Air control	
Manual	✓



Technical data sheet

CARO 120 Soapstone

Air-system	
for room air independent installation	✓

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	200 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
European standard	EN 16510
MINERGIE® compatible	✓
DIBt	Z-43.12.425
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

Technical data sheet

CARO 120 Soapstone

SERVICES

Thermal output	
Nominal heat output	5.5 kW
Fuelwood requirement	1.7 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	12.5 m ³ /h
Triple values	
Exhaust gas mass flow	4.5 g/s
Exhaust temperature	350 °C
Minimum flue draught	-13 Pa
Fire safety	
Dust at 13 % O ₂	≤40 mg/Nm ³
CO emission at 13 % O ₂	≤0.12 %
CO emission at 13 % O ₂	≤1500 mg/Nm ³
OGC at 13 % O ₂	≤120 mg/Nm ³
NO _x at 13 % O ₂	≤200 mg/Nm ³

Note

The declaration of performance in French contains the values for France.
Please note the declarations of performance in the other languages.

Technical data sheet

CARO 120 Soapstone

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Please observe the national/regional regulations for floor protection.