

Technical data sheet

NEXO 100 BIO

Note for Switzerland:

For use without a chimney in Switzerland, the appliances are designed for a maximum output of 2 kW. Please note that different power ratings apply in Switzerland.

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Side window	
Without side window	✓
Two side windows	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Nickel	✓
Sand	✓
Handles	
Oak wood black	✓
«Classic»	✓
Stainless steel	✓
Corian®	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓



Technical data sheet

NEXO 100 BIO

Operating	
Remote control	✓
Attika BIO App	✓
Control panel on the device	✓
Fireplace design	
Amber/black granules	✓
Ceramic-wood set	✓
Combination of amber/black granules and Ceramic-wood set	✓
without decoration	✓

Technical data sheet

NEXO 100 BIO

PRODUCT INFORMATION

General	
Weight depending on model/equipment	120 kg
fireplace connection	
Without a chimney (Please note the comment on the first page)	✓
Power supply	
Power connection	230 V
Safety	
Automatic ignition	✓
automatic pump	✓
Built-in CO2 sensor	✓
Overfill sensor	✓
Overfill sensor	✓
Pressure relief valve	✓
Certifications	
European standard	EN16647
TÜV	✓

 SERVICES IN EU

Technical specifications	
Power (min.-max.)	1.6 - 3.4 kW
Burning time (min.-max.)	14 - 31 h
Fuel tank capacity	7.8 L
Minimum room size	34 m ²

All information is provided without guarantee. Sketches are not true to scale.

06.07.2026 | 3 / 4

Technical data sheet

NEXO 100 BIO

Note Minimum room size:

Please refer to the information in the installation manual.

Safety distances:

Information on safety distances can be found in the installation manual.