

Technical data sheet

Q-TEE 2

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Base unit	
Base unit low	✓
Base unit high	✓
Design feet	
Design feet low	✓
Design feet high	✓
Coating	
Black	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Calf leather brown	✓
Calf leather black	✓
Air control	
Manual	✓
Air-system	
for room air independent installation	✓
Side bench	
Side bench narrow	✓
Side bench wide	✓



Technical data sheet

Q-TEE 2

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	147 - 172 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A+
Multiple occupancy	✓
Eco Design	✓
European standard	EN 16510
MINERGIE® compatible	✓
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

Technical data sheet

Q-TEE 2

SERVICES

Thermal output	
Nominal heat output	6.7 kW
Fuelwood requirement	2 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	15.6 m ³ /h
Triple values	
Exhaust gas mass flow	5.6 g/s
Exhaust temperature	317 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % O ₂	≤40 mg/Nm ³
CO emission at 13 % O ₂	≤0.12 %
CO emission at 13 % O ₂	≤1500 mg/Nm ³
OGC at 13 % O ₂	≤120 mg/Nm ³
NO _x at 13 % O ₂	≤200 mg/Nm ³

Safety distances:

Information on safety distances can be found in the installation manual.