

Technical data sheet

VISIO 100 T

OPTIONS

| | |
|------------------------------|----------|
| Designframe (non supporting) | |
| Black | ✓ |
| Stainless steel | ✓ |
| Anti-reflective glass | |
| Anti-reflective glass | ✓ |
| Operating | |
| Remote control | Standard |
| attika fire app | Option |
| Home Automation | Option |



Technical data sheet

VISIO 100 T

PRODUCT INFORMATION

| Connections | |
|-------------------------------------|-----------------------|
| Flue pipe Ø (LAS) | 130/200 mm |
| Gas connection | Ø 12 mm 1/2" 3/8" |
| Weight depending on model/equipment | |
| Weight depending on model/equipment | 125 - 150 kg |
| Permissible chimney systems | |
| Schiedel Ontop Metaloterm | ✓ |
| Jeremias | ✓ |
| M&G Group | ✓ |
| Poujoulat | ✓ |
| Certifications | |
| Energy efficiency class | A |
| CE | EU 2016/426 |
| SVGW | 19-015-3 |

Technical data sheet

VISIO 100 T

SERVICES

| Output range | |
|--|-----------------------|
| Natural gas G20/20 mbar | 1.1-6.5 kW |
| Propane gas G31/50 mbar | 1.8-8.9 kW |
| Gas consumption | |
| Natural gas G20/20 mbar | 0.9 m ³ /h |
| Propane gas G31/50 mbar | 0.4 m ³ /h |
| Maximum load | |
| Natural gas G20/20 mbar | 8.1 kW |
| Propane gas G31/50 mbar | 11.2 kW |
| Energy efficiency | |
| Efficiency class Natural gas G20/20 mbar | 1 |
| Efficiency class Propane gas G31/50 mbar | 1 |

INSTALLATION

| Furniture distance from the front glass | |
|--|--------|
| A: Furniture distance from the front glass | 500 mm |
| Furniture distance from the side glass | |
| B: Furniture distance from the side glass | 500 mm |

CONVECTION AIR

| | |
|----------------------|---------------------|
| Convection air above | 200 cm ² |
| Convection air below | 200 cm ² |

Technical data sheet

VISIO 100 T

Installation

