

# Technical data sheet

## VISIO 160 3S

### OPTIONS

|                              |          |
|------------------------------|----------|
| Designframe (non supporting) |          |
| Black                        | ✓        |
| Stainless steel              | ✓        |
| Anti-reflective glass        |          |
| Anti-reflective glass        | ✓        |
| Operating                    |          |
| Remote control               | Standard |
| attika fire app              | Option   |
| Home Automation              | Option   |



# Technical data sheet

## VISIO 160 3S

### PRODUCT INFORMATION

| Connections                         |                          |
|-------------------------------------|--------------------------|
| Flue pipe Ø (LAS)                   | 130/200 mm               |
| Gas connection                      | Ø 12 mm   1/2"  <br>3/8" |
| Weight depending on model/equipment |                          |
| Weight depending on model/equipment | 160 - 170 kg             |
| Permissible chimney systems         |                          |
| Schiedel Ontop Metaloterm           | ✓                        |
| Jeremias                            | ✓                        |
| M&G Group                           | ✓                        |
| Poujoulat                           | ✓                        |
| Certifications                      |                          |
| Energy efficiency class             | A                        |
| CE                                  | EU 2016/426              |
| SVGW                                | 19-015-3                 |

# Technical data sheet

## VISIO 160 3S

### SERVICES

| Output range              |                        |
|---------------------------|------------------------|
| Natural gas   G20/20 mbar | 3-17.2 kW              |
| Propane gas   G31/50 mbar | 2.7-16.5 kW            |
| Gas consumption           |                        |
| Natural gas   G20/20 mbar | 2.2 m <sup>3</sup> /h  |
| Propane gas   G31/50 mbar | 0.78 m <sup>3</sup> /h |
| Maximum load              |                        |
| Natural gas   G20/20 mbar | 23.5 kW                |
| Propane gas   G31/50 mbar | 22.4 kW                |
| Energy efficiency         |                        |
| Natural gas   G20/20 mbar | 91.1 %                 |
| Propane gas   G31/50 mbar | 90.5 %                 |

### INSTALLATION

| Furniture distance from the front glass    |        |
|--|--------|
| A: Furniture distance from the front glass | 500 mm |
| Furniture distance from the side glass     |        |
| B: Furniture distance from the side glass  | 500 mm |

### CONVECTION AIR

|                      |                     |
|----------------------|---------------------|
| Convection air above | 700 cm <sup>2</sup> |
| Convection air below | 500 cm <sup>2</sup> |

# Technical data sheet

## VISIO 160 3S

### Installation

