

# Technical data sheet

## VISIO 160 LC/RC

### OPTIONS

Designframe (non supporting)	
Black	✓
Stainless steel	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika fire app	Option
Home Automation	Option



# Technical data sheet

## VISIO 160 LC/RC

### PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm   1/2"   3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	160 - 170 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
Jeremias	✓
M&G Group	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

# Technical data sheet

## VISIO 160 LC/RC

### SERVICES

Output range	
Natural gas   G20/20 mbar	3-17.2 kW
Propane gas   G31/50 mbar	2.7-16.5 kW
Gas consumption	
Natural gas   G20/20 mbar	2.2 m <sup>3</sup> /h
Propane gas   G31/50 mbar	0.78 m <sup>3</sup> /h
Maximum load	
Natural gas   G20/20 mbar	23.5 kW
Propane gas   G31/50 mbar	22.4 kW
Energy efficiency	
Natural gas   G20/20 mbar	91.1 %
Propane gas   G31/50 mbar	90.5 %

### INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	500 mm

### CONVECTION AIR

Convection air above	700 cm <sup>2</sup>
Convection air below	500 cm <sup>2</sup>

# Technical data sheet

## VISIO 160 LC/RC

### Installation

