Technical data sheet
VISIO 160 LC/RC

OPTIONS

Designframe (non supporting)	
Black	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika gas app	Option
Home Automation	Option



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VISIO 160 LC/RC

PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm | 1/2" | 3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	160 - 170 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
Jeremias	✓
M&G Group	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

PRODUCT INFORMATION

Certifications	
SVGW	✓

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VISIO 160 LC/RC

SERVICES

Output range	
Natural gas | G20/20 mbar	3-17.2 kW
Propane gas | G31/50 mbar	2.7-16.5 kW
Gas consumption	
Natural gas | G20/20 mbar	2.2 m^3/h
Propane gas | G31/50 mbar	0.78 m^3/h
Maximum load	
Natural gas | G20/20 mbar	23.5 kW
Propane gas | G31/50 mbar	22.4 kW
Energy efficiency	
Efficiency class Natural gas | G20/20 mbar	1
Efficiency class Propane gas | G31/50 mbar	1

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	500 mm


CONVECTION AIR

Convection air above	700 cm^2
Convection air below	500 cm^2

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VISIO 160 LC/RC

Installation



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch