

Technical data sheet

VISIO 2 ELEMENT

OPTIONS

| | |
|------------------------------|-------|
| Support frame | |
| Black, 6mm | ✓ |
| Stainless steel, 6mm | ✓ |
| Window frame | |
| Black | ✓ |
| Stainless steel | ✓ |
| Handles | |
| Oak wood handle dark stained | ✓ |
| Stainless steel | ✓ |
| Steel black | ✓ |
| Air-system | |
| Air-system | ✓ |
| Additional concrete element | |
| Additional concrete element | 1 stk |



Technical data sheet

VISIO 2 ELEMENT

PRODUCT INFORMATION

| | |
|-------------------------------------|----------|
| Weight depending on model/equipment | |
| Weight depending on model/equipment | 649 kg |
| Ø Smoke outlet | |
| Ø Smoke outlet | 200 mm |
| Ø Air inlet | |
| Ø Air inlet | 150 mm |
| Flue pipe outlet | |
| Top | ✓ |
| Rear | ✓ |
| Certifications | |
| Energy efficiency class | A |
| Eco Design | ✓ |
| EN NORM | EN 13240 |
| BImSchV | Stufe 2 |
| Flamme Verte | 7* |
| Classe energetica di appartenenza | 4 Stelle |

Technical data sheet

VISIO 2 ELEMENT

SERVICES

| Thermal output | |
|---|-------------------------|
| Nominal heat output | 7 kW |
| Thermal output range min./max. | 5-9 kW |
| Fuelwood requirement | 2 ≈ kg/h |
| Energy efficiency | 80 % |
| Combustion air requirement | 23.4 m ³ /h |
| Triple values | |
| Exhaust gas mass flow | 7.6 g/s |
| Exhaust temperature | 243 °C |
| Required delivery pressure | 12 Pa |
| Required delivery pressure at 0.8 times the nominal heat output | 10 Pa |
| Fire safety | |
| Dust at 13 % O ₂ | 5 mg/Nm ³ |
| CO emission at 13 % O ₂ | 0.1 % |
| CO emission at 13 % O ₂ | 1249 mg/Nm ³ |
| OGC at 13 % O ₂ | 54 mg/Nm ³ |
| NO _x at 13 % O ₂ | 82 mg/Nm ³ |

Technical data sheet

VISIO 2 ELEMENT

INSTALLATION

| Distances to combustible materials (without side window) | |
|--|---------|
| C: to the front | 1200 mm |
| D: upwards | 600 mm |
| Distances to combustible materials (with side window) | |
| B: to the side wall | 850 mm |
| C: to the front | 1200 mm |
| D: upwards | 600 mm |

Note

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.

Technical data sheet

VISIO 2 ELEMENT

Sketches of safety distances

