# Technical data sheet
# VISIO 2 ELEMENT

OPTIONS

| | |
|---|---|
| **Support frame** | |
| Black, 6mm | ✓ |
| **Window frame** | |
| Black | ✓ |
| **Handles** | |
| Oak wood handle dark stained | ✓ |
| Stainless steel | ✓ |
| Steel black | ✓ |
| **Air-system** | |
| for room air independent installation | ✓ |
| **Additional concrete element** | |
| Additional concrete element | 1 stk |





ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

# Technical data sheet
# VISIO 2 ELEMENT

PRODUCT INFORMATION

| | |
|---|---|
| **Weight depending on model/equipment** | |
| Weight depending on model/equipment | 649 kg |
| **Ø Smoke outlet** | |
| Ø Smoke outlet | 200 mm |
| **Ø Air inlet** | |
| Ø Air inlet | 150 mm |
| **Flue pipe outlet** | |
| Top | ✓ |
| Rear | ✓ |
| **Certifications** | |
| Energy efficiency class | A |
| Eco Design | ✓ |
| European standard | EN 16510 |
| BImSchV | Stufe 2 |
| Flamme Verte | ✓ |
| Classe energetica di appartenenza | 4 Stelle |



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

# Technical data sheet
# VISIO 2 ELEMENT

SERVICES

| Thermal output | |
|---|---|
| Nominal heat output | 7.9 kW |
| Fuelwood requirement | 2.4 ≈ kg/h |
| Energy efficiency | ≥75 % |
| Combustion air requirement | 23.8 $m^3$/h |
| **Triple values** | |
| Exhaust gas mass flow | 7.9 g/s |
| Exhaust temperature | 299 °C |
| Minimum flue draught | -12 Pa |
| **Fire safety** | |
| Dust at 13 % O2 | ≤40 mg/$Nm^3$ |
| CO emission at 13 % O2 | ≤0.12 % |
| CO emission at 13 % O2 | ≤1500 mg/$Nm^3$ |
| OGC at 13 % O2 | ≤120 mg/$Nm^3$ |
| NOx at 13 % O2 | ≤200 mg/$Nm^3$ |

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch