

# Technical data sheet

## VISIO 2 L

### OPTIONS

Support frame	
Black, 6mm	✓
Stainless steel, 6mm	✓
Window frame	
Black	✓
Stainless steel	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
Air-system	✓
Heat-storage module©	
Heat-storage module©	112 kg



# Technical data sheet

## VISIO 2 L

### PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	353 - 465 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A+
Eco Design	✓
EN NORM	EN 13229
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	3 Stelle

# Technical data sheet

## VISIO 2 L

### SERVICES

Thermal output	
Nominal heat output	10.3 kW
Thermal output range min./max.	8-12 kW
Fuelwood requirement	3 ≈ kg/h
Energy efficiency	81 %
Triple values	
Exhaust gas mass flow	11.3 g/s
Exhaust temperature	225 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O <sub>2</sub>	28 mg/Nm <sup>3</sup>
CO emission at 13 % O <sub>2</sub>	0.098 %
CO emission at 13 % O <sub>2</sub>	1226 mg/Nm <sup>3</sup>
CO <sub>2</sub> concentration	8.7 %
OGC at 13 % O <sub>2</sub>	68 mg/Nm <sup>3</sup>
NO <sub>x</sub> at 13 % O <sub>2</sub>	73 mg/Nm <sup>3</sup>

# Technical data sheet

## VISIO 2 L

### INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1250 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	800 mm

### CONVECTION AIR

Convection air above	min. 750 cm <sup>2</sup>
Convection air below	min. 375 cm <sup>2</sup>

### Note

Maximum weight supported by the frame: 200 kg.

# Technical data sheet

## VISIO 2 L

### Installation

