

# Technical data sheet

## VISIO 3 ELEMENT

### OPTIONS

Support frame	
Black, 6mm	✓
Stainless steel, 6mm	✓
Window frame	
Black	✓
Stainless steel	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
Air-system	✓
Additional concrete element	
Additional concrete element	1 stk



# Technical data sheet

## VISIO 3 ELEMENT

### PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	699 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A
Eco Design	✓
EN NORM	EN 13240
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	4 Stelle

# Technical data sheet

## VISIO 3 ELEMENT

### SERVICES

Thermal output	
Nominal heat output	7 kW
Thermal output range min./max.	5-9 kW
Fuelwood requirement	2 ≈ kg/h
Energy efficiency	80 %
Combustion air requirement	23.4 m <sup>3</sup> /h
Triple values	
Exhaust gas mass flow	7.5 g/s
Exhaust temperature	243 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O <sub>2</sub>	5 mg/Nm <sup>3</sup>
CO emission at 13 % O <sub>2</sub>	0.09 %
CO emission at 13 % O <sub>2</sub>	1150 mg/Nm <sup>3</sup>
OGC at 13 % O <sub>2</sub>	45 mg/Nm <sup>3</sup>
NO <sub>x</sub> at 13 % O <sub>2</sub>	81 mg/Nm <sup>3</sup>

# Technical data sheet

## VISIO 3 ELEMENT

### INSTALLATION

Distances to combustible materials (with side window)	
B: to the side wall	750 mm
C: to the front	1200 mm
D: upwards	500 mm

#### Note

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.

### Sketches of safety distances

