

Technical data sheet

VISIO 3:1 ST

OPTIONS

| | |
|------------------------------|---|
| Support frame | |
| Black, 6mm | ✓ |
| Stainless steel, 6mm | ✓ |
| Window frame | |
| Black | ✓ |
| Stainless steel | ✓ |
| Handles | |
| Oak wood handle dark stained | ✓ |
| Stainless steel | ✓ |
| Steel black | ✓ |
| Air-system | |
| Air-system | ✓ |



Technical data sheet

VISIO 3:1 ST

PRODUCT INFORMATION

| | |
|-------------------------------------|----------|
| Weight depending on model/equipment | |
| Weight depending on model/equipment | 510 kg |
| Ø Smoke outlet | |
| Ø Smoke outlet | 200 mm |
| Ø Air inlet | |
| Ø Air inlet | 150 mm |
| Certifications | |
| Energy efficiency class | A |
| Eco Design | ✓ |
| EN NORM | EN 13229 |
| BImSchV | Stufe 2 |
| Flamme Verte | 7* |
| Classe energetica di appartenenza | 4 Stelle |

Technical data sheet

VISIO 3:1 ST

SERVICES

| Thermal output | |
|---|------------------------|
| Nominal heat output | 10 kW |
| Thermal output range min./max. | 8.7-10 kW |
| Fuelwood requirement | 2.9 ≈ kg/h |
| Energy efficiency | 80 % |
| Triple values | |
| Exhaust gas mass flow | 9.6 g/s |
| Exhaust temperature | 238 °C |
| Required delivery pressure | 12 Pa |
| Required delivery pressure at 0.8 times the nominal heat output | 10 Pa |
| Fire safety | |
| Dust at 13 % O ₂ | 18 mg/Nm ³ |
| CO emission at 13 % O ₂ | 0.0744 % |
| CO emission at 13 % O ₂ | 930 mg/Nm ³ |
| CO ₂ concentration | 8.8 % |
| OGC at 13 % O ₂ | 35 mg/Nm ³ |
| NO _x at 13 % O ₂ | 87 mg/Nm ³ |

Technical data sheet

VISIO 3:1 ST

INSTALLATION

| | |
|--|--------|
| Furniture distance from the front glass | |
| A: Furniture distance from the front glass | 700 mm |
| Furniture distance from the side glass | |
| B: Furniture distance from the side glass | 700 mm |

Note

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.

Sketches of safety distances

