

Technical data sheet

VISIO 70 F

OPTIONS

Designframe (non supporting)	
Black	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika gas app	Option
Home Automation	Option



Technical data sheet

VISIO 70 F

PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm 1/2" 3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	100 - 140 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
Jeremias	✓
M&G Group	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

PRODUCT INFORMATION

Certifications	
SVGW	✓

Technical data sheet

VISIO 70 F

SERVICES

Output range	
Natural gas G20/20 mbar	1.1-7.6 kW
Propane gas G31/50 mbar	1.8-9.1 kW
Gas consumption	
Natural gas G20/20 mbar	0.99 m ³ /h
Propane gas G31/50 mbar	0.5 m ³ /h
Maximum load	
Natural gas G20/20 mbar	9.5 kW
Propane gas G31/50 mbar	11.3 kW
Energy efficiency	
Efficiency class Natural gas G20/20 mbar	1
Efficiency class Propane gas G31/50 mbar	1

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm

CONVECTION AIR

Convection air above	200 cm ²
Convection air below	200 cm ²

Technical data sheet

VISIO 70 F

Installation

