

# Technical data sheet

## VISIO 70 F

### OPTIONS

Designframe (non supporting)	
Black	✓
Stainless steel	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika fire app	Option
Home Automation	Option



# Technical data sheet

## VISIO 70 F

### PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm   1/2"   3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	100 - 140 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
Jeremias	✓
M&G Group	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

# Technical data sheet

## VISIO 70 F

### SERVICES

Output range	
Natural gas   G20/20 mbar	1.1-7.6 kW
Propane gas   G31/50 mbar	1.8-9.1 kW
Gas consumption	
Natural gas   G20/20 mbar	0.99 m <sup>3</sup> /h
Propane gas   G31/50 mbar	0.5 m <sup>3</sup> /h
Maximum load	
Natural gas   G20/20 mbar	9.5 kW
Propane gas   G31/50 mbar	11.3 kW
Energy efficiency	
Efficiency class Natural gas   G20/20 mbar	1
Efficiency class Propane gas   G31/50 mbar	1

### INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm

### CONVECTION AIR

Convection air above	200 cm <sup>2</sup>
Convection air below	200 cm <sup>2</sup>

# Technical data sheet

## VISIO 70 F

### Installation

