

Technical data sheet

VISIO TUNNEL

OPTIONS

Support frame	
Black, 6mm	✓
Window frame	
Black	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
for room air independent installation	✓



Technical data sheet

VISIO TUNNEL

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	235 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Eco Design	✓
European standard	EN 13229
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

One side has a lifting door, the other side is fixed. Both can be tilted for cleaning.

Technical data sheet

VISIO TUNNEL

SERVICES

Thermal output	
Nominal heat output	8.6 kW
Thermal output range min./max.	7.5-8.6 kW
Fuelwood requirement	2.5 ≈ kg/h
Energy efficiency	80 %
Triple values	
Exhaust gas mass flow	7.7 g/s
Exhaust temperature	256 °C
Minimum flue draught	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	24 mg/Nm ³
CO emission at 13 % O ₂	0.071 %
CO emission at 13 % O ₂	887 mg/Nm ³
CO ₂ concentration	9.3 %
OGC at 13 % O ₂	44 mg/Nm ³
NO _x at 13 % O ₂	99 mg/Nm ³

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1200 mm

Technical data sheet

VISIO TUNNEL

CONVECTION AIR

Convection air above	min. 1050 cm ²
Convection air below	min. 525 cm ²

Note

Maximum weight supported by the frame: 200 kg.

Installation

