# Technical data sheet
# VIVA 140 L

OPTIONS

| Firebox door | |
|---|---|
| Steel door | ✓ |
| Glass door | ✓ |
| **Side window** | |
| Without side window | ✓ |
| Two side windows | ✓ |
| **Coating** | |
| Black | ✓ |
| Platinum | ✓ |
| Mocha | ✓ |
| Nickel | ✓ |
| Sand | ✓ |
| **Handles** | |
| Oak wood black | ✓ |
| «classic» | ✓ |
| Stainless steel | ✓ |
| Corian® | ✓ |
| Calf leather brown | ✓ |
| Calf leather black | ✓ |
| Oak nature | ✓ |





ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

# Technical data sheet
# VIVA 140 L

| Top plates | |
|---|---|
| Steel 8 mm | ✓ |
| Steel 28 mm | ✓ |
| Stainless steel | ✓ |
| Soapstone | ✓ |
| **Heat-storage module©** | |
| Heat-storage module© | 48 kg |
| **Air control** | |
| CleverAIR™ | ✓ |
| Manual | ✓ |
| **Air-system** | |
| for room air independent installation | ✓ |
| **Rotating console** | |
| Rotating console | ✓ With a rotating console, smoke outlet is only possible upwards. |
| **Side bench** | |
| Side bench | ✓ |



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

# Technical data sheet
# VIVA 140 L

PRODUCT INFORMATION

| | |
|---|---|
| **Weight depending on model/equipment** | |
| Weight depending on model/equipment | 127 kg |
| **Ø Smoke outlet** | |
| Ø Smoke outlet | 150 mm |
| **Ø Air inlet** | |
| Ø Air inlet | 100 mm |
| **Flue pipe outlet** | |
| Top | ✓ |
| Rear | ✓ |
| **Certifications** | |
| Energy efficiency class | A |
| Multiple occupancy | ✓ |
| Eco Design | ✓ |
| European standard | EN 16510 |
| MINERGIE® compatible | ✓ |
| DIBt | Z-43.12-454 |
| BImSchV | Stufe 2 |
| Flamme Verte | ✓ |
| Classe energetica di appartenenza | 4 Stelle |



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

# Technical data sheet
# VIVA 140 L

SERVICES

| Thermal output | |
|---|---|
| Nominal heat output | 5.5 kW |
| Fuelwood requirement | 1.7 ≈ kg/h |
| Energy efficiency | 76 % |
| Combustion air requirement | 13.6 $m^3$/h |
| **Triple values** | |
| Exhaust gas mass flow | 4.9 g/s |
| Exhaust temperature | 368 °C |
| Minimum flue draught | -12 Pa |
| **Fire safety** | |
| Dust at 13 % 02 | 20 mg/$Nm^3$ |
| CO emission at 13 % 02 | 0.10 % |
| CO emission at 13 % 02 | 1250 mg/$Nm^3$ |
| OGC at 13 % 02 | 80 mg/$Nm^3$ |
| NOx at 13 % 02 | 180 mg/$Nm^3$ |

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Please observe the national/regional regulations for floor protection.



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch