

Technical data sheet

VIVA 140 L GAS

OPTIONS

| | |
|----------------------|-------|
| Firebox door | |
| Steel door | ✓ |
| Glass door | ✓ |
| Side window | |
| Without side window | ✓ |
| Two side windows | ✓ |
| Coating | |
| Black | ✓ |
| Platinum | ✓ |
| Mocha | ✓ |
| Nickel | ✓ |
| Sand | ✓ |
| White | ✓ |
| Top plates | |
| Steel 8 mm | ✓ |
| Steel 28 mm | ✓ |
| Stainless steel | ✓ |
| Soapstone | ✓ |
| Heat-storage module© | |
| Heat-storage module© | 50 kg |
| Side bench | |
| Side bench (VIVA L) | ✓ |



Technical data sheet

VIVA 140 L GAS

| Operating | |
|-----------------|----------|
| Remote control | Standard |
| attika fire app | Option |
| Home Automation | Option |

Technical data sheet

VIVA 140 L GAS

PRODUCT INFORMATION

| Connections | |
|-------------------------------------|-----------------------|
| Flue pipe Ø (LAS) | 100/150 mm |
| Gas connection | Ø 12 mm 1/2" 3/8" |
| Flue pipe outlet | |
| Top | ✓ |
| Rear | ✓ |
| Weight depending on model/equipment | |
| Weight depending on model/equipment | 90 - 130 kg |
| Permissible chimney systems | |
| Schiedel Ontop Metaloterm | ✓ |
| Jeremias | ✓ |
| M&G Group | ✓ |
| Poujolat | ✓ |
| Certifications | |
| Energy efficiency class | A |
| CE | EU 2016/426 |
| SVGW | 18-035-3 |

Technical data sheet

VIVA 140 L GAS

SERVICES

| Output range | |
|--|------------------------|
| Natural gas G20/20 mbar | 1.2-6.4 kW |
| Propane gas G31/50 mbar | 1.3-5.8 kW |
| Gas consumption | |
| Natural gas G20/20 mbar | 0.84 m ³ /h |
| Propane gas G31/50 mbar | 0.29 m ³ /h |
| Maximum load | |
| Natural gas G20/20 mbar | 9.1 kW |
| Propane gas G31/50 mbar | 8 kW |
| Energy efficiency | |
| Efficiency class Natural gas G20/20 mbar | 2 |
| Efficiency class Propane gas G31/50 mbar | 2 |

Technical data sheet

VIVA 140 L GAS

INSTALLATION

| Distances to combustible materials (without side window) | |
|--|---------|
| A: to the back | 50 mm |
| B: to the side wall | 250 mm |
| C: to the front | 700 mm |
| D: upwards | 1000 mm |
| Distances to combustible materials (with side window) | |
| A: to the back | 50 mm |
| B: to the side wall | 300 mm |
| C: to the front | 700 mm |
| D: upwards | 1000 mm |

Technical data sheet

VIVA 140 L GAS

Sketches of safety distances

