attika
FEUERKULTUR

Technical data sheet
VIVA L oven

OPTIONS

Firebox door	
Steel door	✓
Side window	
Without side window	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Nickel	✓
Sand	✓
White	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Corian®	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓
Top plates	
Steel 8 mm	✓
Air control	
Manual	✓



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VIVA L oven

Air-system	
for room air independent installation	✓

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	140 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Rear	✓
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
European standard	EN 16510
MINERGIE® compatible	✓
DIBt	Z-43.12-425
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VIVA L oven

SERVICES

Thermal output	
Nominal heat output	5.5 kW
Fuelwood requirement	1.7 ≈ kg/h
Energy efficiency	76 %
Combustion air requirement	13.6 m^3/h
Triple values	
Exhaust gas mass flow	4.9 g/s
Exhaust temperature	368 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % 02	20 mg/Nm^3
CO emission at 13 % 02	0.10 %
CO emission at 13 % 02	1250 mg/Nm^3
OGC at 13 % 02	80 mg/Nm^3
NOx at 13 % 02	180 mg/Nm^3

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Please observe the national/regional regulations for floor protection.

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch