

UK DECLARATION OF PERFORMANCE
Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01



No.: 127

- | | |
|---|---|
| 1. Unique identification code of the product-type | RAIS VISIO Uniq 3-sided model - ATTIKA VISIO Uniq 3-sided Model |
| 2. Type | Inset appliance burning solid fuel without hot water supply |
| 3. Intended use | Domestic room heater |
| 4. Manufacturer | Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, www.spartherm.com |
| 5. Authorised representative | RAIS A/S, Industrivej 20, Vangen, DK-9900 Frederikshavn, Denmark, www.rais.com / www.attika.ch |
| 6. System of assessment AVCP | System 3 |
| 7. Notified body | The notified laboratory <i>Danish Technological Institute - Identification no. 1235 Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C</i> performed the determination of the product type on the basis of type testing under system 3 and issued test report
a. 300-ELAB-2564-EN |
| 8. Declared performance | Harmonized technical specification: EN 13229:2001/A2:2004/AC:2007 |

Essential characteristics		Performance
Fire safety		<ul style="list-style-type: none"> Insulated flue 50 mm Skamotec 225 non-combustible panel board Distances are measured externally on the built-in box
Reaction to fire	A1	Visio Uniq 3-sided model
Distance to combustible materials	rear	0
Minimum distances [mm]	sides	650
<i>For other installation or wall settings see instruction manual</i>	ceiling	250
	Front	1000
	Floor	400
Risk of burning fuel falling out	Pass	
OGC (mg/Nm ³ rel. 13 Vol-% O ₂)	57	
CO-emission of combustion products	0,07 % / 893 mg/Nm ³	
NO _x (mg/Nm ³ rel. 13 Vol-% O ₂)	113	
Dust mg/Nm ³ at (rel. 13 Vol-% O ₂)	23	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	228 °C	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	9,3 kW	
Room heating output	9,3 kW	
Water heating output	- kW	
Energy efficiency ¹⁷	78 %	
Seasonal Efficiency $\eta_{S,on}$	68 %	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date 14-09-2022


 Signature