

**UK DECLARATION OF PERFORMANCE**  
**Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01**



**No.: 226**

- |   |   |
|---|---|
| 1. Unique identification code of the product-type | RAIS Visio 2-1<br>Attika Visio 2-1  |
| 2. Type   | Inset appliance burning solid fuel without hot water supply   |
| 3. Intended use                                   | Domestic room heater  |
| 4. Manufacturer                                   | Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, <a href="http://www.spartherm.com">www.spartherm.com</a>   |
| 5. Authorised representative                      | RAIS A/S, Industrivej 20, Vangen, DK-9900 Frederikshavn, <u>Dänemark</u> , <a href="http://www.rais.com/">www.rais.com/</a> / <a href="http://www.attika.ch">www.attika.ch</a>  |
| 6. System of assessment AVCP                      | System 3  |
| 7. Notified body                                  | The notified laboratory <i>Danish Technological Institute - Identification no. 1235 Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C</i><br>performed the determination of the product type on the basis of type testing under system 3 and issued test report<br>a. 300-ELAB-2241-EN-B-DIN_Plus |
| 8. Declared performance                           | Harmonized technical specification: EN 13229:2001/A2:2004/AC:2007   |

Essential characteristics		Performance
Fire safety		<ul style="list-style-type: none"> <li>Insulated flue</li> <li>50 mm Skamotec 225 non-combustible panel board</li> </ul> Distances are measured externally on the built-in box
Reaction to fire	A1	<b>Visio 2-1</b>
Distance to combustible materials	rear	-
Minimum distances [mm] <i>For other installation or wall settings see instruction manual</i>	sides	350
	ceiling	1182
	Front	1200
	Floor	475
Risk of burning fuel falling out	Pass	
OGC (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	44	
CO-emission of combustion products	0,071 % / 887 mg/Nm <sup>3</sup>	
NO <sub>x</sub> (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	99	
Dust mg/Nm <sup>3</sup> at (rel. 13 Vol-% O <sub>2</sub> )	24	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	256 °C	
Mechanical resistance (to carry a chimney/flue)	NPD	
<b>Thermal output</b>		
Nominal heat output	8,6 kW	
Room heating output	8,6 kW	
Water heating output	- kW	
Energy efficiency <sup>17</sup>	80 %	
Seasonal Efficiency $\eta_{S,on}$	70 %	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date 14-09-2022

  
 Signature