

## UK DECLARATION OF PERFORMANCE

CPR 2011 (Retained EU law 305/2011) as amended

**No.: 834**

- |  |  |   |  |
|--|--|---|--|
| <b>1. Unique identification code of the product-type</b> | RAIS Q-TEE II C  |   |  |
| <b>2. Type</b>   | Room heater burning solid fuel without hot water supply  |   |  |
| <b>3. Intended use</b>                                   | Domestic room heater   |   |  |
| <b>4. Manufacturer</b>                                   | RAIS A/S<br>Industrivej 20, Vangen<br>DK-9900 Frederikshavn,<br>Denmark  | Telephone +45 98 47 90 33<br>Telefax +45 98 47 92 91<br>Webmail kundeservice@rais.dk<br>Homepage www.rais.com |  |
| <b>5. Authorised representative</b>                      | n/a  |   |  |
| <b>6. System of assessment AVCP</b>                      | System 3   |   |  |
| <b>7. Approved Body</b>                                  | Approved Body – Kiwa Ltd No. 0558 and Report Number  |   |  |
|  | performed the determination of the product type on the basis of type testing under system 3 and issued test report |   |  |
| <b>8. Declared performance</b>                           | Harmonized technical specification:  | EN 13240:2003/A2:2004   |  |

Essential characteristics		Performance	
<b>Fire safety</b>			
Reaction to fire	A1	Uninsulated flue	Insulated flue
Distance to combustible materials	rear	300 (With reflector plate 200)	200
Minimum distances [mm] <i>For other installation or wall settings see instruction manual</i>	sides	400	400
	ceiling	800	800
	Front	1200	1200
Risk of burning fuel falling out	Pass		
OGC (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	63		
CO-emission of combustion products	0,079 %		
NO <sub>x</sub> (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	30		
Dust at (rel. 13 Vol-% O <sub>2</sub> )	14 mg/Nm <sup>3</sup>		
Surface temperature	Pass		
Electrical safety	NPD		
Cleanability	Pass		
Maximum operating pressure	- bar		
Flue gas temperature T at nominal heat output	263° C		
Mechanical resistance (to carry a chimney/flue)	NPD		
<b>Thermal output</b>			
Nominal heat output	6,5 kW		
Room heating output	6,5 kW		
Water heating output	- kW		
Energy efficiency $\eta$	81 %		
Seasonal Efficiency $\eta_{S, on}$	71 %		

- 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D / Quality Manager

**Place** FREDERIKSHAVN, DENMARK

**Date** 02-04-2024

  
 -----  
 Signature